


1600 Series



Size													Rated load(N)		Weight(kg)
select	Inquiry	No.	d		D		B				Chamfering		Cr	Cor	
			mm	inch	mm	inch	Open Type		Shielded Type		rsmin (r)				
							mm	inch	mm	inch	mm	inch			
1601	4.762	0.1875	17.462	0.6875	6.35	0.25	7.938	0.3125	0.3	0.012	1970	730	0.007		
1602	6.35	0.25	17.462	0.6875	6.35	0.25	7.938	0.3125	0.3	0.012	1970	730	0.0065		
1603	7.938	0.3125	22.225	0.875	7.144	0.2813	8.731	0.3437	0.3	0.012	3290	1360	0.012		
1604	9.525	0.375	22.225	0.875	7.144	0.2813	8.731	0.3437	0.4	0.016	3330	1410	0.0105		
1605	7.938	0.3125	23.019	0.9063	7.938	0.3125	7.938	0.3125	0.3	0.012	3330	1410	0.016		
1606	9.525	0.375	23.019	0.9063	7.938	0.3125	7.938	0.3125	0.4	0.016	3330	1410	0.015		
1607	11.112	0.4375	23.019	0.9063	7.938	0.3125	7.938	0.3125	0.4	0.016	2690	1270	0.015		
1614	9.525	0.375	28.575	1.125	9.525	0.375	9.525	0.375	0.6	0.024	5110	2390	0.03		
1615	11.112	0.4375	28.575	1.125	9.525	0.375	9.525	0.375	0.6	0.024	5110	2390	0.028		
1616	12.7	0.5	28.575	1.125	9.525	0.375	9.525	0.375	0.6	0.024	5110	2390	0.026		
1620	11.112	0.4375	34.925	1.375	11.112	0.4375	11.112	0.4375	0.6	0.024	7450	3700	0.05		
1621	12.7	0.5	34.925	1.375	11.112	0.4375	11.112	0.4375	0.6	0.024	7450	3700	0.048		
1622	14.288	0.5625	34.925	1.375	11.112	0.4375	11.112	0.4375	0.6	0.024	7450	3700	0.046		
1623	15.875	0.625	34.925	1.375	11.112	0.4375	11.112	0.4375	0.6	0.024	7450	3700	0.041		
1628	15.875	0.625	41.275	1.625	12.7	0.5	12.7	0.5	0.6	0.024	9390	5020	0.072		
1630	19.05	0.75	41.275	1.625	12.7	0.5	12.7	0.5	0.6	0.024	9390	5020	0.069		
1633	15.875	0.625	44.45	1.75	12.7	0.5	12.7	0.5	0.6	0.024	9390	5020	0.092		
1635	19.05	0.75	44.45	1.75	12.7	0.5	12.7	0.5	0.6	0.24	9390	5020	0.09		
1638	19.05	0.75	50.8	2	14.288	0.5625	14.288	0.5625	0.9	0.035	10060	5860	0.145		
1640	22.225	0.875	50.8	2	14.288	0.5625	14.288	0.5625	0.9	0.035	10060	5860	0.133		
1641	25.4	1	50.8	2	14.288	0.5625	14.288	0.5625	0.9	0.035	10060	5860	0.121		
1652	28.575	1.125	63.5	2.5	15.875	0.625	15.875	0.625	0.9	0.035	19460	11310	0.211		
1654	31.75	1.25	63.5	2.5	15.875	0.625	15.875	0.625	0.9	0.035	19460	11310	0.193		
1657	31.75	1.25	65.087	2.5625	17.462	0.6875	17.462	0.6875	0.9	0.035	19460	11310	0.232		
1658	33.337	1.3125	65.087	2.5625	17.462	0.6875	17.462	0.6875	0.9	0.035	19460	11310	0.21		