



16000 Series



select	Inquiry	No.	Size										Rated load(N)		Weight(kg)
			d		D		B				Chamfering		Cr	Cor	
			mm	inch	mm	inch	Open Type		Shielded Type		rsmin (r)				
							mm	inch	mm	inch	mm	inch			
16100	10	0.3937	28	1.1024	8	0.315	8	0.315	0.3	0.012	5110	2380	0.022		
16101	12	0.4724	30	1.1811	8	0.315	8	0.315	0.3	0.012	5110	2380	0.023		
16001	12	0.4724	28	1.1024	7	0.2756	7	0.2756	0.3	0.012	4320	2250	0.024		
16002	15	0.5906	32	1.2598	8	0.315	8	0.315	0.3	0.012	5590	2840	0.025		
16003	17	0.6693	35	1.378	8	0.315	8	0.315	0.3	0.012	6000	3250	0.032		
16004	20	0.7874	42	1.6535	8	0.315	8	0.315	0.3	0.012	6340	3790	0.05		
16005	25	0.9843	47	1.8504	8	0.315	8	0.315	0.3	0.012	6940	4600	0.06		
16006	30	1.1811	55	2.1654	9	0.3543	9	0.3543	0.3	0.012	9950	6530	0.085		
16007	35	1.378	62	2.4409	9	0.3543	9	0.3543	0.3	0.012	10820	7830	0.11		
16008	40	1.5748	68	2.6772	9	0.3543	9	0.3543	0.3	0.012	11590	9130	0.125		
16009	45	1.7717	75	2.9528	10	0.3937	10	0.3937	0.6	0.024	11830	9880	0.17		
16010	50	1.9685	80	3.1496	10	0.3937	10	0.3937	0.6	0.024	12510	11100	0.18		
16011	55	2.1654	90	3.5433	11	0.4331	11	0.4331	0.6	0.024	19300	16300	0.26		
16012	60	2.3622	95	3.7402	11	0.4331	11	0.4331	0.6	0.024	20000	17500	0.28		
16013	65	2.5591	100	3.937	11	0.4331	11	0.4331	0.6	0.024	21200	17800	0.3		
16014	70	2.7559	110	4.3307	13	0.5118			0.6	0.024	29100	25000	0.44		
16015	75	2.9528	115	4.5276	13	0.5118			0.6	0.024	22100	22000	0.46		
16016	80	3.1496	125	4.9213	14	0.5511			0.6	0.024	32000	3000	0.6		
16017	85	3.3465	130	5.1181	14	0.5511			0.6	0.024	33500	30000	0.63		
16018	90	3.5433	140	5.5118	16	0.6299			1	0.0393	41500	39300	0.84		
16019	95	3.7402	145	5.7087	16	0.6299			1	0.0393	42700	41900	0.88		
16020	100	3.937	150	5.9055	16	0.6299			1	0.0393	43800	44300	0.91		
16021	105	4.1339	160	6.2992	18	0.7087			1	0.0393	51800	50600	1.23		
16022	110	4.3307	170	6.6929	19	0.748			1.5	0.059	57400	56700	1.47		
16024	120	4.7244	180	7.2834	19	0.748			2	0.0787	58800	60400	1.82		
16026	130	5.1181	200	7.874	22	0.8661			2	0.0787	79700	79200	2.32		
16028	140	5.1181	210	8.2677	22	0.8661			2	0.0787	82600	85000	2.5		

16000 Series

16030	150	5.905	225	8.852	24	0.9449			2	0.0787	91900	98500	2.62
16032	160	6.2992	240	9.4488	25	0.9843			2	0.0787	98700	10700	4.61
16034	170	6.1929	260		28	1.1023			2.5	0.0984	100000	130000	5.83