
71800 series



select	Inquiry	Part Number	Bore diameter	Outside diameter	Width	Contact angle	Matched arrangement	Preload	Seal type	Ring material	Ball material	Radial dynamic load rating	Radial static load rating	Limiting speed
71800 CD/P4	10 mm	19 mm	5 mm	15 °	Single	Available	Open	Chrome Steel	Chrome Steel	428 lbf	220 lbf	120 X 1000 rpm		
71800 CDGA/P4	10 mm	19 mm	5 mm	15 °	Single	Extra light / Class A	Open	Chrome Steel	Chrome Steel	428 lbf	220 lbf	95 X 1000 rpm		
71800 CDGB/P4	10 mm	19 mm	5 mm	15 °	Single	Light / Class B	Open	Chrome Steel	Chrome Steel	428 lbf	220 lbf	95 X 1000 rpm		
71800 ACD/P4	10 mm	19 mm	5 mm	25 °	Single	Available	Open	Chrome Steel	Chrome Steel	400 lbf	209 lbf	110 X 1000 rpm		
71800 ACDGA/P4	10 mm	19 mm	5 mm	25 °	Single	Extra light / Class A	Open	Chrome Steel	Chrome Steel	400 lbf	209 lbf	95 X 1000 rpm		
71800 ACDGB/P4	10 mm	19 mm	5 mm	25 °	Single	Light / Class B	Open	Chrome Steel	Chrome Steel	400 lbf	209 lbf	95 X 1000 rpm		
71800 CD/P4DBA	10 mm	19 mm	10 mm	15 °	Duplex Back-to-Back (DB)	Extra light / Class A	Open	Chrome Steel	Chrome Steel	691 lbf	441 lbf	95 X 1000 rpm		
71800 CD/P4DBB	10 mm	19 mm	10 mm	15 °	Duplex Back-to-Back (DB)	Light / Class B	Open	Chrome Steel	Chrome Steel	691 lbf	441 lbf	95 X 1000 rpm		
71800 CD/P4DBC	10 mm	19 mm	10 mm	15 °	Duplex Back-to-Back (DB)	Moderate / Class C	Open	Chrome Steel	Chrome Steel	691 lbf	441 lbf	95 X 1000 rpm		
71800 CD/P4DGA	10 mm	19 mm	10 mm	15 °	Universal Matchable (SU)	Extra light / Class A	Open	Chrome Steel	Chrome Steel	691 lbf	441 lbf	95 X 1000 rpm		
71800 CD/P4DGAVT105F2	10 mm	19 mm	10 mm	15 °	Universal Matchable (SU)	Extra light / Class A	Open	Chrome Steel	Chrome Steel	691 lbf	441 lbf	95 X 1000 rpm		
71800 CD/P4DGB	10 mm	19 mm	10 mm	15 °	Universal Matchable (SU)	Light / Class B	Open	Chrome Steel	Chrome Steel	691 lbf	441 lbf	95 X 1000 rpm		
71800 ACD/P4DBB	10 mm	19 mm	10 mm	25 °	Duplex Back-to-Back (DB)	Light / Class B	Open	Chrome Steel	Chrome Steel	655 lbf	418 lbf	95 X 1000 rpm		
71800 ACD/P4DFA	10 mm	19 mm	10 mm	25 °	Duplex Face-to-Face (DF)	Extra light / Class A	Open	Chrome Steel	Chrome Steel	655 lbf	418 lbf	95 X 1000 rpm		
71800 ACD/P4DFBVT162F2	10 mm	19 mm	10 mm	25 °	Duplex Face-to-Face (DF)	Light / Class B	Open	Chrome Steel	Chrome Steel	655 lbf	418 lbf	95 X 1000 rpm		
71800 ACD/P4DGA	10 mm	19 mm	10 mm	25 °	Universal Matchable (SU)	Extra light / Class A	Open	Chrome Steel	Chrome Steel	655 lbf	418 lbf	95 X 1000 rpm		
71800 ACD/P4DGB	10 mm	19 mm	10 mm	25 °	Universal Matchable (SU)	Light / Class B	Open	Chrome Steel	Chrome Steel	655 lbf	418 lbf	95 X 1000 rpm		
71801 CD/P2	12 mm	21 mm	5 mm	15 °	Single	Available	Open	Chrome Steel	Chrome Steel	468 lbf	266 lbf	110 X 1000 rpm		
71801 CD/P4	12 mm	21 mm	5 mm	15 °	Single	Available	Open	Chrome Steel	Chrome Steel	468 lbf	266 lbf	110 X 1000 rpm		
71801 CDGA/P4	12 mm	21 mm	5 mm	15 °	Single	Extra light / Class A	Open	Chrome Steel	Chrome Steel	468 lbf	266 lbf	140 X 1000 rpm		
71801 CDGB/P4	12 mm	21 mm	5 mm	15 °	Single	Light / Class B	Open	Chrome Steel	Chrome Steel	468 lbf	266 lbf	140 X 1000 rpm		

71801 ACD/P4	12 mm	21 mm	5 mm	25 °	Single	Available	Open	Chrome Steel	Chrome Steel	439 lbf	252 lbf	95 X 1000 rpm
71801 ACDGA/P4	12 mm	21 mm	5 mm	25 °	Single	Extra light / Class A	Open	Chrome Steel	Chrome Steel	439 lbf	252 lbf	100 X 1000 rpm
71801 ACDGB/P4	12 mm	21 mm	5 mm	25 °	Single	Light / Class B	Open	Chrome Steel	Chrome Steel	439 lbf	252 lbf	100 X 1000 rpm
71801 ACDGB/P4VT105	12 mm	21 mm	5 mm	25 °	Single	Light / Class B	Open	Chrome Steel	Chrome Steel	439 lbf	252 lbf	100 X 1000 rpm
71801 CD/P4DBA	12 mm	21 mm	10 mm	15 °	Duplex Back-to-Back (DB)	Extra light / Class A	Open	Chrome Steel	Chrome Steel	760 lbf	531 lbf	110 X 1000 rpm
71801 CD/P4DBB	12 mm	21 mm	10 mm	15 °	Duplex Back-to-Back (DB)	Light / Class B	Open	Chrome Steel	Chrome Steel	760 lbf	531 lbf	110 X 1000 rpm
71801 CD/P4DGA	12 mm	21 mm	10 mm	15 °	Universal Matchable (SU)	Extra light / Class A	Open	Chrome Steel	Chrome Steel	760 lbf	531 lbf	140 X 1000 rpm
71801 ACD/P4DBB	12 mm	21 mm	10 mm	25 °	Duplex Back-to-Back (DB)	Light / Class B	Open	Chrome Steel	Chrome Steel	718 lbf	504 lbf	100 X 1000 rpm
71801 ACD/P4DFBVT162F2	12 mm	21 mm	10 mm	25 °	Duplex Face-to-Face (DF)	Light / Class B	Open	Chrome Steel	Chrome Steel	718 lbf	504 lbf	100 X 1000 rpm